

# MULTI SPLIT



## Unità Interne ZEAS



Telecomando

Modello	Unità interna		SFM-09ZES2-AU1	SFM-12ZES2-AU1	SFM-18ZES2-AU1
Capacità	Raffrescamento	Btu/h	8871 (4780-11260)	12285 (5800-12625)	17747 (8530-19790)
		kW	2.60 (0.6-3.1)	3.50 (1.70-3.70)	5.27 (2.50-5.80)
	Riscaldamento	Btu/h	8905 (4095-10240)	12625 (5120-12625)	18085 (7680-19790)
		kW	2.61(0.80-3.40)	3.50(1.50-3.70)	5.37(2.25-5.80)
Dati elettrici	Alimentazione	V~,Hz,Ph	220-240,50,1	220-240,50,1	220~240,50,1
	Assorbimento in raffrescamento	W	40(12~68)	40(12~68)	63(16~88)
	Assorbimento in riscaldamento	W	40(12~68)	40(12~68)	63(16~88)
Motore Ventola	Potenza	W	18	18	30
	Velocità	r/min	1250	1250	1330
Performance	Portata d'aria	m3/h	600	600	850
	Pressione sonora (max/med/min)	dB(A)	40/36/32	41/36/33	44/41/35
	Potenza sonora	dB(A)	54	52	57
Dimensioni	Dimensioni nette (L*P*H)	mm	690 x 199 x 283	750 x 200 x 285	900 x 225 x 310
	Dimensioni imballo (L*P*H)	mm	760 X 347x277	820 x 277x 347	970 x 302 x 382
Peso	Netto	kg	7	8,5	11
	Lordo	kg	9	10,5	13
Refrigerante			R32	R32	R32
Diametro tubi	Lato liquido	mm(inch)	6.35(1/4)	6.35(114)	6.35(114)
	Lato gas	mm(inch)	9.52(3/8)	9.52(318)	12.7(112)
	Drenaggio	mm	16,5	16,5	16,5

Note: SENDO si riserva il diritto di cambiare i dati tecnici in tabella senza preavviso.

